

Attico STORE

TYRE PRODUCT MANUAL

中兴慧通

轮胎产品手册

Attico STORE

АДРЕС

Московская область, Ленинский
городской округ, промзона
Пуговичино, вл8

ТЕЛЕФОН

+7 (495) 669-35-62

E-MAIL

a-store@attico.ru

РЕЖИМ РАБОТЫ

Пн. – Пт.: с 9:00 до 18:00

OTRSTAR
世世达

HERADE
与瑞达

新飞亚

COMPANY HONORS

企业荣誉 >>>>>>>>



CORE SELLING POINTS

核心卖点 >>>>>>>>



轮胎含胶量高达 58%

远超行业平均水平，
耐磨性提升15%，使用更长久



生产工艺稳定

4+3+128次检查
四大车间班组检测，质量、技术、
安检轮检，128个检查项目



30 年制造经验

1992年建厂，专业研发、生产斜交轮胎，
累计开发规格3000个，持有**OTRSTAR (傲世达)**、
HERADE (亨瑞达)、**新飞亚**等知名品牌。



真层级

拒绝层级虚标
载重更强，使用更安全



合作背书

工程机械头部企业配套
国内外知名品牌代工
每年经过多次验厂



PRODUCT CONTENTS

产品目录 >>>>>>>>

叉车胎 21-22

滑移装载机 23-25

工业雪地胎 26

高空作业胎 27

港口胎 28

挖掘机轮胎 29-30

军工胎 31-32

工业拖拉机轮胎 33-34

载重汽车胎 39-41

房车胎 42



装载机轮胎 11-12

平地机轮胎 13

铲运机轮胎 14

压路机轮胎 15

矿用填充胎 16

矿用载重胎 17

矿山胎 18-20

农业胎 35-37

运粮车胎 38



LOADER TIRE 装载机轮胎

1. 横向大块花纹设计, 提供优异的驱动性能;
1. Horizontal large pattern design provides excellent driving performance.
2. 中部加强筋设计, 提高轮胎抗冲击花掉块能力;
2. The design of reinforced ribs in the middle enhances the tire's ability to resist chipping and chipping.
3. 专用耐磨配方, 同时搭配合理的节距设计, 轮胎花纹深度及接地面积加大, 大大提升轮胎耐磨性能, 延长轮胎使用寿命;
3. Special wear-resistant formula, combined with reasonable pitch design, increases the pattern depth and ground contact area, greatly improving the wear resistance and extending the service life.
4. 采用高强度胎体帘线, 胎侧强度大幅增加;
4. The use of high-strength fabric cord significantly increases the sidewall strength.
5. 胎面采用双补强设计, 轮胎承载性能大幅提高。
5. The tread uses a double reinforcement design, greatly improving the tire's load-bearing performance.

E3/L3 HT236

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
16/70-20-14	TT	17	10/A2	1075	410	13	450	5150
16/70-24-14	TT	22	10/A2	1175	410	13	450	5600
17.5-25-16	TT/TL	26	10/A2	1350	445	14.00/1.5	475	7300
17.5-25-20	TT/TL	26	10/A2	1350	445	14.00/1.5	575	8250
17.5-25-24	TT/TL	26	10/A2	1350	445	14.00/1.5	700	9250
20.5-25-20	TT/TL	30	10/A2	1490	520	17.00/2.0	450	9500
20.5-25-24	TT/TL	30	10/A2	1490	520	17.00/2.0	525	10300
20.5-25-28	TT/TL	30	10/A2	1490	520	17.00/2.0	625	11500
23.5-25-16	TT/TL	35	10/A2	1615	595	19.50/2.5	300	9500
23.5-25-20	TT/TL	35	10/A2	1615	595	19.50/2.5	375	10900
23.5-25-24	TT/TL	35	10/A2	1615	595	19.50/2.5	475	12500
23.5-25-28	TT/TL	35	10/A2	1615	595	19.50/2.5	550	13600



GTR L-3 SC

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
26.5-25-28	TT/TL	35	10/A2	1750	675	22.00/3.0	475	15500
26.5-25-32	TT/TL	35	10/A2	1750	675	22.00/3.0	550	17000
29.5-25-28	TT/TL	38	10/A2	1875	750	25.00/3.5	425	17500
29.5-25-32	TT/TL	38	10/A2	1875	750	25.00/3.5	525	17000

HT239P

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
23.5-25-20	TT/TL	30	10/A2	1582	587	19.50/2.5	375	10900
23.5-25-24	TT/TL	30	10/A2	1582	587	19.50/2.5	475	12500



E3/L3 HT239

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
17.5-25-16	TT/TL	24	10/A2	1330	417	14.00/1.5	475	7300
17.5-25-20	TT/TL	24	10/A2	1330	417	14.00/1.5	575	8250
17.5-25-24	TT/TL	24	10/A2	1330	417	14.00/1.5	700	9250
23.5-25-20	TT/TL	30	10/A2	1570	565	19.50/2.5	375	10900
23.5-25-24	TT/TL	30	10/A2	1570	565	19.50/2.5	475	12500



GRADER TIRE 平地机轮胎

1. 较深且具有方向性的花纹, 使轮胎具有较好的牵引性能和较好的自洁性能。

1. Deeper and directional patterns give tires good traction and self-cleaning performance.

2. 宽胎面的设计提供了良好的浮力, 使其在泥泞的路面具有优异的驱动性能。

2. The wide tread design provides good buoyancy, giving it excellent driving performance on muddy roads.



L-3S

L-4S/5S

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10.00-20-14	TT	29	10/A2	1055	280	7.5	700	4750
12.00-24-16	TT	31	10/A2	1275	315	8.5	675	6150
12.00-24-20	TT	40	10/A2	1275	315	8.5	825	6900
12.00-24-24	TT	40	10/A2	1275	315	8.5	975	7500
14.00-24-24	TT	45	10/A2	1370	375	10.00/2.0	850	9500
17.5-25-20	TT	58	10/A2	1400	445	14.00/1.5	575	8250
17.5-25-24	TT	58	10/A2	1400	445	14.00/1.5	700	9250
17.5-25-20	TT	63	10/A2	1400	445	14.00/1.5	575	8250
17.5-25-24	TL	63	10/A2	1400	445	14.00/1.5	700	9250
18.00-25-32	TL	78	10/A2	1675	500	13.00/2.5	750	15000
18.00-25-40	TL	78	10/A2	1675	500	13.00/2.5	950	17000

G-2

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
13.00-24-12	TL	25	40/AB	1280	355	8.00TC	300	2725
14.00-24-16	TL	25	40/AB	1350	360	8.00TC	375	3650
15.5-25-12	TL	24	40/AB	1275	395	12.00/1.3	225	2650
17.5-25-16	TL	29	40/AB	1350	445	14.00/1.3	275	3350



SCRAPER TIRE 铲运机轮胎

1. 适用于使用条件极度苛刻的井巷、隧道等多岩石条件下作业。

1. Suitable for operations under extremely harsh conditions such as shafts, tunnels, and other multi-rock conditions.

2. 加强胎体, 加厚胎面, 使轮胎的负荷能力得到显著的提升。

2. Strengthen the tire body, thicken the tread, and significantly improve the tire's load capacity.

3. 采用高强度、高硬度专用胎面配方, 使轮胎具有良好的耐切割、抗刺穿能力和耐磨性。

3. Adopting a high-strength and high-hardness specialized tread formula, the tire has good cutting resistance, puncture resistance, and wear resistance.



ROLLER TIRE 压路机轮胎

1. 胎面采用特殊的胶料配方，使轮胎具有良好的抗刺扎、耐磨性能。
1. The tread adopts a special rubber formula, which makes the tire have good puncture resistance and wear resistance.
2. 平滑的加厚、超加厚胎面，增加了对沙石的抗刺穿能力。
2. Smooth thickened and extra thickened tread increases resistance to sand and gravel penetration.



MINING FILLING TIRE 矿用填充胎

1. 适用于使用条件极为苛刻的井巷、隧道等多岩石条件下作业。
1. Suitable for operations under extremely harsh conditions such as shafts, tunnels, and other multi-rock conditions.
2. 超强胎体，加厚胎面，高强度、高硬度专用胎面配方，使轮胎具有良好的耐切割、抗刺穿能力和耐磨性。
2. Super strong tire body, thickened tread, high strength, and high hardness special tread formula, making the tire have good cutting resistance, puncture resistance, and wear resistance.
3. 特殊的行驶面和花纹设计，轮胎行驶稳定，具有极好的通过性能。
3. Special driving surface and pattern design ensure stable tire driving and excellent passability.



C-1

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD GAUGE	气压 PRESSURE (kPa)	负荷 LOAD
7.50-15-6	TT	12	10/A2	785	215	6	400	1850
7.50-15-12	TT	12	10/A2	785	215	6	750	2650
7.50-15-14	TT	12	10/A2	785	215	6	875	2900
11.00-20-16	TT	16	10/A2	1090	290	8	725	5450
13/80-20-18	TT	18	10/A2	1060	320	8.5	900	6000

HT901

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD GAUGE	气压 PRESSURE (kPa)	负荷 LOAD
8.00-20-16	TT	30	10/A2	900	240	6.5	1200	4775
8.25-20-18	TT	30	10/A2	970	265	6.5	980	5280
36X12.5-20-28	TT	33	10/A2	915	320	11	1500	6875
40X12.5-20-32	TT	33	10/A2	1020	330	11	1500	7220
60X25-25-52	TT	45	10/A2	1525	650	19.5	1800	33035



MINING TRUCK TIRE 矿用载重胎

1. 专为非公路用自卸车车辆设计，胎体的加强，胎体坚固、抗爆、耐刺扎，具有超强的负荷能力；
1. Specially designed for the off-highway dump truck, the tire body is reinforced, sturdy, anti-explosion, puncture resistant, and has super strong load capacity.
2. 特殊胎面耐磨配方和低生热配方设计，具有优异的耐切割性能和耐磨性能。
2. Special tread wear-resistant formula and low heat generation formula design, with excellent cutting resistance and wear resistance.
3. 独特的深花纹设计和宽行路面设计，爬坡不打滑，通过性能优异。
3. Unique deep pattern design and wide driving surface design, without slipping when climbing, with excellent performance.



MINE MOUNTAIN TIRE 矿山胎

1. 大花纹块的设计增强了轮胎的抓着力；
1. The design of large pattern blocks enhances the grip of the tire.
2. 加深花纹的设计，提高了轮胎的使用寿命；
2. Deepening the design of the pattern improves the service life of the tire.
3. 独特的配方设计，使轮胎具有了优良的抗割伤和耐刺扎性能。
3. The unique formula design makes the tire with excellent cut and puncture resistance.



HT233

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD MM	气压 PRESSURE (KPa)	负荷 LOAD
10.00-20-24	TT	28	20/A4	1055	378	7.5	1000	4800
11.00-20-18	TT	24	10/A2	1105	293	8	910	3650
11.00-20-20	TT	24	10/A2	1105	293	8	1000	3875
12.00-20-18	TT	25	10/A2	1145	315	8.5	775	5800
12.00-20-20	TT	25	10/A2	1145	315	8.5	825	6150
13.00-25-32	TT	26	10/A2	1300	350	10.00/1.5	1200	10000
14.00-20-24	TT	25	10/A2	1265	375	10	850	8500
14.00-24-28	TT	28	10/A2	1370	375	10.00/2.0	925	10000
14.00-24-32	TT	28	10/A2	1370	375	10.00/2.0	1050	10900
14.00-25-32	TT	28	10/A2	1370	375	10.00/2.0	1050	10900
14.00-25-36	TT	28	10/A2	1370	375	10.00/2.0	1200	11500
16.00-25-40	TT	32	10/A2	1495	430	11.25/2.0	1075	14500

HT310

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD MM	气压 PRESSURE (KPa)	负荷 LOAD
6.50-16-14	TT	17	50B	785	200	5.50F	730	1320/1180
7.00-16-14	TT	17	50B	785	200	5.50F	730	1320/1180
7.50-16-14	TT	17	50B	816	215	6.00G	730	1500/1320
8.25-16-16	TT	18	50B	867	235	6.50H	730	1800/1600
10.00-20-16	TT	28	50B	1073	278	7.5	810/740	3000/2650
11.00-20-18	TT	28	50B	1105	293	8	910/840	3650/3150
12.00-20-20	TT	28	50B	1145	315	8.5	880/810	4000/3450



ST988

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (KPa)	负荷 LOAD
9.00-20-16	TT	20	25A5	1038	295	7	880/810	2900/2500
11.00-20-18	TT	21	25A5	1105	293	8	910/840	3650/3150
12.00-20-18	TT	23	25A5	1145	315	8.5	810/740	3750/3450
12.00-24-18	TT	22	25A5	1247	315	8.5	810/740	4250/3750



HT322

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (KPa)	负荷 LOAD
14.00-20-24	TT	25	50B	1265	375	10	850	8500
14.00-20-20	TT	25	50B	1265	375	10	770/700	5000/4375

HT316

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (KPa)	负荷 LOAD
7.00-16-14	TT	21	50B	785	200	5.50F	730	1320/1180
7.50-16-16	TT	22	50B	816	215	6.00G	830	1650/1450
8.25-16-16	TT	23	50B	840	235	6.50H	925	2520



HT222

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (KPa)	负荷 LOAD
11.00-20-18	TT	24	50B	1105	293	8	910/840	3650/3150
12.00-20-18	TT	26	50B	1145	315	8.5	810/740	3750/3350





FORKLIFT TIRE 叉车胎

1. 采用特殊的配方设计使轮胎具有良好的抗切割及耐磨性能;
1. ADOPTING A SPECIAL FORMULA DESIGN TO MAKE THE TIRE HAVE GOOD CUTTING RESISTANCE AND WEAR RESISTANCE;
2. 大块的花纹设计赋予轮胎优良的抓地性能;
2. THE LARGE PATTERN DESIGN ENDOWS THE TIRE WITH EXCELLENT GRIP PERFORMANCE;
3. 胎体特别加强, 负荷大, 行驶面宽, 行驶平稳。
3. THE TIRE BODY IS PARTICULARLY STRENGTHENED, WITH A HIGH LOAD, A WIDE TRAVEL SURFACE, AND SMOOTH DRIVING.



C601 驱动轮/转向轮

规格 SIZE	有无内胎 TY/C	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD RIM	气压 PRESSURE (kg/cm ²)	负荷 LOAD
18X7-8-16	TT	17	25/A5	465	173	4.33R	1000	1695/1450
21X8-9-14	TT	16	25/A5	535	200	6.00E	1000	2040/1725
23X9-10-16	TT	20	25/A5	595	225	6.50F	1030	2810/2370
23X10-12-16	TT	20	25/A5	597	254	6.00G	970	3220/2720
23X10-12-20	TT	20	25/A5	597	254	8.00G	790	3160
27X10-12-24	TT	23	25/A5	690	255	8.00G	1000	3770
4.00-8-8	TT	13	25/A5	415	112	3.00D	930	745/630
5.00-8-10	TT	14	25/A5	470	137	3.50D	1000	1150/970
6.00-9-10	TT	16	25/A5	540	160	4.00E	860	1505/1275
6.50-10-12	TT	18	25/A5	590	175	5.00F	1000	1895/1600
7.00-12-12	TT	18	25/A5	676	190	5.00S	860	2375/2005
7.00-12-14	TT	18	25/A5	676	190	5.00S	1000	2590/2190
250-15-20	TT	20	25/A5	735	250	7.50B0	1000	5000
28X9-15-14	TT	19	25/A5	706	220	7.00B0	970	3050/2575
7.00-15-12	TT	20	25/A5	750	200	5.5	860	2870/2420
7.00-15-14	TT	20	25/A5	750	200	5.5	1000	3140/2655
7.50-15-12	TT	20	25/A5	780	215	6.00G	790	3075/2680
7.50-16-16	TT	20	25/A5	805	215	6.00G	950	3225
8.25-15-14	TT	20	25/A5	840	235	6.50B0	830	3775/3185
300-15-20	TT	24	25/A5	840	300	8.00B0	930	6575/5790
9.00-20-14	TT	30	25/A5	1018	259	7	760	5195/4385
9.00-20-16	TT	30	25/A5	1018	259	7	860	5595/4725
10.00-20-16	TT	34	25/A5	1055	278	7.5	790	6030/5090
11.00-20-16	TT	36	25/A5	1085	293	8	760	6405/5405
12.00-20-20	TT	38	25/A5	1125	315	8.5	1000	7400/6325
12.00-24-20	TT	38	25/A5	1225	315	8.5	1000	6140
14.00-24-28	TT	38	25/A5	1343	375	10	1000	12850



C602 驱动轮/转向轮

规格 SIZE	有无内胎 TY/C	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD RIM	气压 PRESSURE (kg/cm ²)	负荷 LOAD
6.00-9-10	TT	14	25/A5	540	160	4.00E	860	1505/1275
6.50-10-10	TT	15	25/A5	590	175	5.00F	790	1655/1400
7.00-12-12	TT	16	25/A5	676	190	5.00S	860	2375/2005
28X9-15-14	TT	16	25/A5	706	220	7	970	3050/2575
7.00-15-12	TT	17	25/A5	750	200	5.5	860	2870/2420
8.25-15-14	TT	17	25/A5	840	235	6.5	830	3775/3185

C603 驱动轮/转向轮

规格 SIZE	有无内胎 TY/C	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD RIM	气压 PRESSURE (kg/cm ²)	负荷 LOAD
6.00-9-10	TT	16	25/A5	540	160	4.00E	860	1505/1275
6.00-9-12	TT	16	25/A5	540	160	4.00E	1030	1675/1415
6.50-10-10	TT	17	25/A5	590	175	5.00F	790	1655/1400
6.50-10-12	TT	17	25/A5	590	175	5.00F	1000	1895/1600
7.00-12-12	TT	18	25/A5	676	190	5.00S	860	2375/2005
7.00-12-14	TT	18	25/A5	676	190	5.00S	1000	2590/2190
28X9-15-14	TT	18	25/A5	706	220	7	970	3050/2575
8.25-15-14	TT	19	25/A5	840	235	6.5	830	3775/3185
8.25-15-16	TT	19	25/A5	840	235	6.5	925	4050/3450



C604(HT606) 驱动轮/转向轮

规格 SIZE	有无内胎 TY/C	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮距 STANDARD RIM	气压 PRESSURE (kg/cm ²)	负荷 LOAD
5.00-8-10	TT	13	25/A5	470	137	3.50D	1000	1150/970
6.00-9-10	TT	16	25/A5	540	160	4.00E	860	1505/1275
6.50-10-10	TT	15	25/A5	590	175	5.00F	790	1655/1400
6.50-10-14	TT	15	25/A5	590	175	5.00F	790	1655/1400
7.00-12-12	TT	18	25/A5	676	190	5.00S	860	2375/2005
28X9-15-14	TT	15	25/A5	706	220	7	970	3050/2575
28X9-15-16	TT	15	25/A5	706	220	7	970	3050/2575
8.25-15-14	TT	17	25/A5	840	235	6.5	830	3775/3185
23X9-10-16	TT	15	25/A5	595	225	6.50F	1030	2810/2370
18X7-8-14	TT	14	25/A5	465	173	4.33R	970	1505/1270



SKID STEER LOADER TIRE 滑移装载机

1. 适合于特殊使用条件的车辆，具有优异的抓地力性能、抗湿滑性能和耐磨性能。
SUITABLE FOR VEHICLES WITH SPECIAL USAGE CONDITIONS, IT HAS EXCELLENT TRACTION PERFORMANCE, WET ROAD RESISTANCE AND WEAR RESISTANCE.
2. 独特的花纹设计，使轮胎不易夹带泥沙和石子，具有良好的自洁性，通过性能优异；
THE UNIQUE PATTERN DESIGN MAKES IT SPECIAL FOR THE TIRE TO CARRY SAND AND STONES, AND HAS GOOD SELF-CLEANING PERFORMANCE, WITH EXCELLENT PERFORMANCE.
3. 特殊形式的轮胎保护设计。
SPECIAL FORM OF TIRE PROTECTION DESIGN.



X-ROAD

规格 SIZE	有无内胎 T/F/L	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
12-16.5-12	TL	30	50/B	831	307	9.75	550	2865
14-17.5-14	TL	34	50/B	921	349	10.5	550	3875

T602



规格 SIZE	有无内胎 T/F/L	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
12.5/80-18-10	TL	18	10/A2	965	308	9	310	2375
14-17.5-10	TL	16	10/A2	921	349	10.5	380	3105
15-19.5-6	TL	21	10/A2	1019	389	11.75	140	2250



T601(HT601)

规格 SIZE	有无内胎 T/F/L	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
10-16.5-10	TL	17	10/A2	773	264	8.25	520	2135
10-16.5-12	TL	15	10/A2	760	253	8.25	620	2375
12-16.5-10	TL	18	10/A2	815	295	9.75	450	2575
12-16.5-12	TL	20	10/A2	831	307	9.75	550	2865
23X8 50-12-8	TL	13	10/A2	574	213	7.00J	450	975
27X8 50-15-8	TL	14	10/A2	678	213	7LB	410	1305
27X10-12-14	TL	19	25/A5	690	255	8.00G	700	2725
14-17.5-14	TL	26	10/A2	921	349	10.5	550	3875
15-19.5-14	TL	26	10/A2	1019	389	11.75	485	4565
27X10.5-15-8	TL	16	10/A2	691	259	8LB	410	1405
700-15-6	TL	17	25/A5	750	200	5.5	410	1450
700-15-8	TL	17	10/A2	750	200	5.5	520	1650
570-12-6	TL	14	10/A2	570	146	4.5	520	750
31X15 50-15-8	TL	24	50/B	792	391	12	310	1250
33X15.5-16.5-14	TL	20	10/A2	831	389	12	410	3100



T603

规格 SIZE	有无内胎 T/F/L	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
10-16.5-8	TL	19	10/A2	773	264	8.25	410	1880
10-16.5-10	TL	19	10/A2	773	264	8.25	520	2135
12-16.5-12	TL	21	10/A2	831	307	9.75	550	2865
14-17.5-14	TL	22	10/A2	921	349	10.5	550	3875
15-19.5-14	TL	23	10/A2	1019	389	11.75	485	4565

HT616



规格 SIZE	有无内胎 T/F/L	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
10-16.5-10	TL	15	10/A2	760	253	8.25	520	2135
12-16.5-12	TL	18	10/A2	815	295	9.75	550	2865

T604 XD2010

规格 SIZE	有无内胎 T/F/L	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
10-16.5-8	TL	18	10/A2	773	264	8.25	410	1880
10-16.5-10	TL	18	10/A2	773	264	8.25	520	2135
12-16.5-10	TL	18	10/A2	831	307	9.75	450	2540
12-16.5-12	TL	18	10/A2	831	307	9.75	550	2865





T605 SK770

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10-16.5-8	TL	16	10/A2	773	264	8.25	410	1880
12-16.5-10	TL	17	10/A2	831	307	9.75	450	2540

T607 L4

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10-16.5-12	TL	34	10/A2	773	264	8.25	620	2375
12-16.5-14	TL	34	10/A2	831	307	9.75	620	3075



T608(L-5 HT608)

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10-16.5-10	TL	35	10/A2	790	268	8.25	520	2135
12-16.5-12	TL	35	10/A2	836	315	9.75	550	2865
14-17.5-14	TL	37	10/A2	932	358	10.5	550	3875
12.5/80-18-12	TL	28	10/A2	965	308	9	310	2375



T613(BOOMER)

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10-16.5-8	TL	18	10/A2	773	264	8.25	410	1880
12-16.5-10	TL	22	10/A2	831	307	9.75	450	2540



INDUSTRIAL SNOW TIRE 工业雪地胎

1. 雪地轮胎通过特殊的配方来增大与冰雪路面的摩擦力，提高了冰雪路面的通过性和安全性。
1. SNOW TIRES USE SPECIAL FORMULAE TO INCREASE FRICTION WITH ICE AND SNOWY ROADS, IMPROVING THEIR PASSABILITY AND SAFETY.
2. 特殊的花纹设计有助于排除积水、雪、泥炭和冰，减少打滑风险。
2. SPECIAL PATTERN DESIGN HELPS TO ELIMINATE ACCUMULATED WATER, SNOW, MUD, AND ICE, REDUCING THE RISK OF SLIPPING.



EKT-2

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10-16.5-10	TL	30	10/A2	773	264	8.25	410	1880
12-16.5-12	TL	30	10/A2	831	307	9.75	550	2865
14-17.5-14	TL	30	10/A2	921	349	10.5	550	3875
16.9-24-14	TL	24	10/A2	1335	430	W15L	260	2610
16.9-28-14	TL	24	10/A2	1435	430	W15L	300	4840
19.5L-24-12	TL	28	10/A2	1340	495	DW16	210	2145
21.5L-24-16	TL	28	10/A2	1450	576	DW18	250	2795



AERIAL WORK TIRE 高空作业胎

1. 适合于特殊使用条件的车辆，具有优异的路面抓着力、抗湿滑性能和耐磨性能。
1. VEHICLES SUITABLE FOR SPECIAL USAGE CONDITIONS, WITH EXCELLENT ROAD GRIP PERFORMANCE, WET TRIP RESISTANCE, AND WEAR RESISTANCE.
2. 独特的花纹设计，不易夹带泥沙和石子，具有良好的自洁性，通过性能优异。
2. UNIQUE PATTERN DESIGN, NOT EASY TO CARRY SEDIMENT AND STONES, WITH GOOD SELF-CLEANING PERFORMANCE, EXCELLENT PERFORMANCE.



PORT TIRE 港口胎

1. 高深道胎面花纹设计，提供强大的牵引力。
1. High depth tread pattern design provides strong traction.
2. 合理的花纹节距及高饱和度胎冠设计搭配冠壁高设计，胎冠更平坦，更耐偏磨。
2. Reasonable pattern pitch and high saturation tread crown design combined with crown wall height design make the tread flatter and more resistant to eccentric wear.
3. 加厚胎体，加强胎体及侧包设计，承载能力更强，稳定性大幅提升，大大提升了轮胎的使用性能和抗刺扎能力。
3. Thickening the tire bodywall, strengthening the tire body and side package design, enhancing the load-bearing capacity, significantly enhancing stability, and greatly improving the tire's performance and anti-puncture ability.
4. 采用专用耐磨胎面配方及低生热基料配方，轮胎更耐磨生热性更低，轮胎使用寿命更长。
4. By using a dedicated wear-resistant tread formula and a low heat-generating base rubber formula, the tire is more wear-resistant and has lower heat generation, resulting in a longer service life.



R-4 HT688

规格 SIZE	有无内胎 TY/TL	花纹深度 DEPT (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准胎宽 STANDARD WID	气压 PRESSURE (kPa)	负荷 LOAD
315/55020-12	TL	20	10/A2	820	320	20X11	560	2900
355/550625-14	TL	21	10/A2	936	360	11.75	520	3450
355/550625-16	TL	21	10/A2	936	360	11.75	700	4625
385/65072.5-18	TL	25	10/A2	1018	397	11.75	690	4935
18-625-16	TL	22	10/A2	1018	397	11.75	800	6900
445/500710-18	TL	23	10/A2	1189	445	W15	590	7300
445/500710-20	TL	23	10/A2	1189	445	W15	790	7740

IND-4

规格 SIZE	有无内胎 TY/TL	花纹深度 DEPT (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准胎宽 STANDARD WID	气压 PRESSURE (kPa)	负荷 LOAD
12.00-24-24	TT	43	25/A5	1245	315	8.5	975	7500
14.00-24-28	TT/TL	53	25/A5	1370	375	10.00/2.0	925	10000
14.00-24-32	TT/TL	53	25/A5	1370	375	10.00/2.0	1050	10900
18.00-25-40	TL	68	25/A5	1615	500	13.00/2.5	950	17000





EXCAVATOR TIRE 挖掘机轮胎

1. 采用特殊的配方，具有优异的路面抓着力、抗湿滑性能和耐磨性能。
1. ADOPTING A SPECIAL FORMULA, IT HAS EXCELLENT ROAD GRIP PERFORMANCE, MOISTURE RESISTANCE, AND WEAR RESISTANCE.
2. 花纹设计独特，不易夹带泥沙和石子，具有良好的自洁性，通过性能优异。
2. THE UNIQUE PATTERN DESIGN IS NOT EASY TO CARRY MUD AND STONES, AND HAS GOOD SELF-CLEANING PROPERTIES WITH EXCELLENT PERFORMANCE.
3. 较深且具有方向性的花纹赋予轮胎良好的牵引性能和导向性能。
3. THE DEEP AND DIRECTIONAL PATTERN ENDOWS THE TIRE WITH GOOD TRACTION AND GUIDANCE PERFORMANCE.
4. 独特的胎面设计使轮胎在松软、泥泞和坎坷的路面具有优异的驱动性能。
4. THE UNIQUE TREAD DESIGN GIVES THE TIRE EXCELLENT DRIVING PERFORMANCE ON SOFT, MUDDY, AND BUMPY ROADS.

HT601(HT816)

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
8.25-20-14	TT	19	50/B	974	236	6.5	810	2240
8.25-20-16	TT	19	50/B	974	236	6.5	910	2430
9.00-20-14	TT	20	50/B	1018	259	7	770	2575
9.00-20-16	TT	20	50/B	1018	259	7	880	2900
10.00-20-16	TT	21	50/B	1055	278	7.5	810	3000
11.00-20-16	TT	22	50/B	1085	293	8	810	3350



HT319

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
9.00-20-14	TT	28	50/B	1018	259	7	700	2300
9.00-20-18	TT	28	50/B	1018	259	7	810	2500

HT818

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
10.00-20-16	TT	28	50/B	1055	278	7.5	810	3000



HT869

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
8.25-16-16	TT	18	50B	855	235	6.50H	730	1800/1600

HT810

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
7.50-16-14	TT	22	50/B	805	215	6.00G	730	1500
8.25-16-16	TT	22	50/B	855	235	6.50H	730	1800





MILITARY INDUSTRY TIRE 军工胎

1. 较深且具有方向性的花纹，使轮胎具有较好的牵引性能和较好的自洁性能。
1. DEEP AND DIRECTIONAL PATTERNING GIVE TIRES GOOD TRACTION AND SELF-CLEANING PERFORMANCE.
2. 宽胎面的设计提供了良好的浮力，使其在泥泞的路面具有优异的驱动性能。
2. THE WIDE TREAD DESIGN PROVIDES GOOD BUOYANCY, GIVING IT EXCELLENT DRIVING PERFORMANCE ON MUDDY ROADS.
3. 采用高强度、高硬度专用胎面配方，使轮胎具有良好的耐切割、抗刺穿能力和耐磨性。
3. ADOPTING A HIGH-STRENGTH AND HIGH-HARDNESS SPECIALIZED TREAD FORMULA, THE TIRE HAS GOOD CUTTING RESISTANCE, PUNCTURE RESISTANCE, AND WEAR RESISTANCE.



T19

规格 SIZE	有无内胎 TT/TL	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
13-20-18	TT	40/A8	1210	385	11.00V	420	3700

YB018

规格 SIZE	有无内胎 TT/TL	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
1300X530-533	TT	40/A8	1300	533	440-533	660	5980



VG-MX

规格 SIZE	有无内胎 TT/TL	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
14.00-20-20	TT	40/A8	1265	375	10	770/700	5000/4375





INDUSTRIAL TRACTORS TIRE 工业拖拉机轮胎

1. 胎体进行加强，胎体更加坚固，防碾、耐刺扎，具有更强的负荷能力；
1. Strengthen the fetal body, making it more sturdy, crush-proof, puncture-resistant, and with stronger load capacity.
2. 采用特殊的胎面耐磨配方和低生热配方，使胎面具有了优良的耐切割性能和耐磨性能；
2. Adopting a special tread wear-resistant formula and low heat generation formula, the tread has excellent cutting resistance and wear resistance.
3. 特殊的深花纹设计和宽行波面的设计，让轮胎爬坡时的抓地力变得更强，通过性能优异；
3. The special deep pattern design and wide wave surface design make the tire's grip stronger when climbing hills, resulting in excellent performance.



R-4

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
14.9-24-12	TL	19	40/A8	1265	378	W13	300	2380
17.5L-24-10	TL	27	40/A8	1265	445	W15L	190	1725
18.4-24-10	TL	28	40/A8	1374	447.5	W16L	210	3350
19.5L-24-12	TL	27	40/A8	1340	495	DW16	210	2145
21L-24-12	TL	28	40/A8	1400	533	DW18	190	2410
21L-24-16	TL	28	40/A8	1400	533	DW18	250	2795



R-4 N707

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
12.5/80-18-12	TL	25	40/A8	985	308	9	370	2625

EKR4

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
12.5/80-18-12	TL	25	40/A8	985	308	9	370	2625



EKR4

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
16.9-24-12	TL	25	40/A8	1335	430	W15L	260	3550
16.9-28-12	TL	27	40/A8	1435	430	W15L	260	3550
19.5L-24-12	TL	27	40/A8	1340	495	DW16	210	2145
18.4-26-12	TL	29	40/A8	1450	467	DW16	230	2985

EKR4

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
405/70-20-16	TL	36	40/A8	1075	410	13	350	2600
405/70-24-16	TL	35	40/A8	1175	410	13	270	5600
405/70-24-24	TL	35	40/A8	1175	410	13	490	8750





AGRICULTURE TYRE 农业胎

1. 较深且具有方向性的花纹赋予轮胎强大的抓地能力和良好的牵引性能;
1. THE DEEP AND DIRECTIONAL PATTERN ENDOWS THE TYRE WITH STRONG GRIP AND GOOD TRACTION PERFORMANCE.
2. 加宽的胎面, 具有良好的浮力, 具有优异的沙地路面的通过性能;
2. THE WIDENED TREAD HAS GOOD BUOYANCY AND EXCELLENT PASSING PERFORMANCE ON SANDY ROADS.
3. 宽胎面, 圆胎肩的设计, 使其在行驶过程中能够保持平稳。
3. THE DESIGN OF WIDE TREAD AND ROUND SHOULDER ENSURES STABILITY DURING DRIVING.



R3

规格 SIZE	有无内胎 TYE	花纹深度 DEEP (mm)	速度/速度级别 SPEED SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
33X15.50-16.5-10	TL	14	10/A2	831	389	12	240	2260
33X15.50-16.5-12	TL	14	10/A2	831	389	12	415	3900
26X12-12-8	TL	12	10/A2	648	307	10.5	340	1370
31X13.50-15-12	TL	11	10/A2	792	351	10.5	520	2530

规格 SIZE	有无内胎 TYE	花纹深度 DEEP (mm)	速度/速度级别 SPEED SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
31X15.50-15-8	TL	20	10/A2	810	401	12	310	1975
31X15.50-15-10	TL	20	10/A2	810	401	12	410	2215

I-3



N702(I-1)

规格 SIZE	有无内胎 TYE	花纹深度 DEEP (mm)	速度/速度级别 SPEED SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
7.60-15-8	TL	6	50/B	740	176	5.5	390	710
9.5L-15-8	TL	8	50/B	765	240	7	280	1100
11L-15-8	TL	8	50/B	775	280	8	220	1130
11L-15-12	TL	8	50/B	775	280	8	620	1800
12.5L-15-10	TL	8	50/B	823	318	W10L	620	2122
16.5L-16.1-10	TL	12	50/B	1025	420	16.1X14LB	220	2360
16.5L-16.1-14	TL	12	50/B	1025	420	16.1X14LB	300	2900
31X13.50-15-12	TL	10	50/B	792	351	10LB	520	2530

IMP-02



规格 SIZE	有无内胎 TYE	花纹深度 DEEP (mm)	速度/速度级别 SPEED SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (PSI)	负荷 LOAD
500/50-17-14	TL		40/A8	950	500	AG16.00	200	1800
500/50-17-18	TL		40/A8	950	500	AG16.00	480	4125
400/60-22.5-18	TL		40/A8	1070	400	AG13.00	430	3150
500/45-22.5-16	TL		40/A8	1048	485	AG16.00	360	3075
500/60-22.5-16	TL		40/A8	1170	500	AG16.00	320	3450
500/60-22.5-18	TL		40/A8	1170	500	AG16.00	360	3650
550/45-22.5-16	TL		40/A8	1070	530	AG16.00	280	3750
550/45-22.5-18	TL		40/A8	1070	530	AG16.00	320	4000
550/60-22.5-16	TL		40/A8	1238	550	AG16.00	280	3750
550/60-22.5-18	TL		40/A8	1238	550	AG16.00	320	4000
600/50-22.5-16	TL		40/A8	1170	576	AG20.00	260	3650
600/50-22.5-20	TL		40/A8	1170	576	AG20.00	325	5150
700/40-22.5-16	TL		40/A8	1180	710	AG24.00	220	3750
700/40-22.5-20	TL		40/A8	1180	710	AG24.00	270	
600/55-26.5-16	TL		40/A8	1333	591	AG20.00	260	4375
700/50-26.5-16	TL		40/A8	1333	700	AG24.00	240	4750
800/45-26.5-16	TL		40/A8	1333	800	AG28.00	220	5000
800/45-26.5-20	TL		40/A8	1333	800	AG28.00	270	
650/65-30.5-16	TL		40/A8	1670	650	AG20.00	220	5450
850/50-30.5-16	TL		40/A8	1670	850	AG28.00	220	6700
850/50-30.5-18	TL		40/A8	1670	850	AG28.00	250	8000



R-1



规格 SIZE	有无内胎 TY/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
30.5L-32-18	TL	56	40/A8	1820	775	DW27A	190	5000
18.4-38-12	TL	43	40/A8	1755	467	W16L	230	3575
18.4-38-16	TL	43	40/A8	1755	467	W16L	350	4575
11.2-24-8	TL	34	40/A8	1105	285	W10	240	1225
800/65-32-20	TL	56	40/A8	1870	800	DW27A	320	7750
900/60-32-20	TL	56	40/A8	1900	900	DW27A	320	9250
15.5/80-24-16	TL	38	40/A8	1240	395	W13	400	3300
18.4-30-8	TL	43	40/A8	1550	467	W16L	140	2415
18.4-30-12	TL	43	40/A8	1550	467	W16L	230	3180
18.4-34-10	TL	38	40/A8	1655	467	W16L	180	2990
16.9-28-10	TL	38	40/A8	1435	430	W15L	200	2380
16.9-26-10	TL	35	40/A8	1385	430	W15L	200	2305
23.1-26-16	TL	43	40/A8	1605	587	DW20	240	4460
14.9-28-10	TL	35	40/A8	1365	378	W13	230	2120
12.4-24-8	TL	34	40/A8	1160	315	W11	230	1415
14.9-24-8	TL	33	40/A8	1265	378	W13	180	1760
18.4-28-8	TL	39	40/A8	1500	467	W16L	140	2310
18.4-28-12	TL	39	40/A8	1500	467	W16L	220	3135
12.4-24-12	TL	33	40/A8	1160	315	W11	330	1775
14.9-24-10	TL	33	40/A8	1265	378	W13	230	1990
24.5-32-16	TL	35	40/A8	1805	622	DW21A	250	4875
24.5-32-14	TL	45	40/A8	1805	622	DW21A	190	4375
11.2-28-8	TL	32	40/A8	1205	128	W10	240	1305
12.4-28-8	TL	33	40/A8	1260	315	W11	230	1510
16.9-30-10	TL	35	40/A8	1485	430	W15L	200	2455
20.8-38	TL	40	40/A8	1835	528	W18L	160	3475
13.6-28-8	TL	34	40/A8	1310	345	W12	210	1645
18.4-42-16	TL	43	40/A8	1857	467	W16L	320	4750
23.1-30-12	TL	40	40/A8	1705	587	DW20	170	3850
16.9-24-8	TL	35	40/A8	1335	430	W15L	170	2040



GRAIN TRUCK TIRE 运粮车胎

1. 具有较好的耐磨性能，独特的胎面设计，大大提高了使用寿命。
1. Has good wear resistance and unique tread design, greatly extending service life.

HT702

规格 SIZE	有无内胎 TY/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
19.0/45-17-14	TL	12	40/A8	866	491	16	280	2800
19.0/45-17-14	TL	13	40/A8	866	491	16	280	2800
500/50-17-14	TL	14	40/A8	932	503	16	280	3250
10.0/75-15.3-10	TL	9	40/A8	760	264	W9	390	1525
11.5/80-15.3-10	TL	9	40/A8	845	290	9	340	1930
12.5/80-15.3-14	TL	9	40/A8	869	307	9	430	2650
13.0/65-18-16	TL	12	40/A8	890	336	11	490	2750
15.0/70-18-12	TL	13	40/A8	990	391	13	310	2890



TRUCK TIRE 载重汽车胎

- 1. 较深的花纹设计, 提高了抓地性能;
1. Deeper pattern design enhanced grip performance.
- 2. 较宽的行驶面, 具有良好的耐磨性能。
2. Wide driving surface with good wear resistance.



ST888

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
6.00-14-8	TT	13	90G	680	170	4.5J	420	690/600
6.50-14-8	TT	14	90G	705	180	4.5J	420	775/690
7.00-15-8/10	TT	14	90G	750	200	5.50F	420	900/800
7.00-15-12	TT	14	90G	750	200	5.50F	630	1150/1030
6.00-16-6	TT	14	90G	730	170	4.50E	320	630/560
6.50-16-8	TT	14	90G	750	185	5.50F	420	850/750
7.00-16-8	TT	15	90G	775	200	5.50F	530	1090/950
7.00-16-10	TT	15	90G	775	200	5.50F	530	1090/950
7.50-16-8	TT	16	90G	805	215	6.00G	420	1120/975
7.50-16-14	TT	16	90G	805	215	6.00G	730	1500/1320

CM-57/58

规格 SIZE	有无内胎 TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
8.00-16.5-8	TL	12	100J	720	203	6	410	925/825
8.75-16.5-8	TL	12	100J	748	222	6	410	1090/950





RIB/LUG

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
6.00-13-8	TT	11	90G	655	170	4.50B	420	650/580
6.00-14-8	TT	8	90G	680	170	4.5J	420	690/600
6.50-14-10	TT	8	90G	705	180	4.5J	530	900/800
6.50-16-12	TT	10	90G	750	185	5.50F	630	1060/925
7.00-16-12	TT	11	90G	775	200	5.50F	630	1215/1060
7.00-16-14	TT	11	90G	775	200	5.50F	730	1320/1180
6.50-15-10	TT	10	90G	730	180	4.50E	530	950/825
7.00-15-12	TT	11	90G	750	200	5.50F	630	1150/1030
7.50-15-12	TT	12	90G	780	215	6.00G	630	1360/1215
7.50-15-14	TT	12	90G	780	215	6.00G	730	1450/1285
7.50-16-14	TT	12	90G	805	215	6.00G	730	1500/1320
8.25-16-14	TT	13	90G	855	235	6.50H	630	1700/1500
8.25-16-16	TT	13	90G	855	235	6.50H	730	1800/1600
8.25-20-14	TT	14	90G	974	236	6.5	810/740	2240/1950
8.25-20-16	TT	14	90G	974	236	6.5	910/840	2430/2180
9.00-20-14	TT	15	90G	1018	259	7	770/700	2575/2300
9.00-20-16	TT	15	90G	1018	259	7	880/810	2900/2500
10.00-20-16	TT	15	90G	1055	278	7.5	810/740	3000/2650
10.00-20-18	TT	15	90G	1055	278	7.5	910/840	3350/2900
11.00-20-16	TT	16	90G	1085	293	8	810/740	3350/2900
12.00-20-18	TT	16	90G	1125	315	8.5	810/740	3750/3350

ST935

规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
11.00-20-18	TT	17	25A5	1085	293	8	910/840	3650/3150
12.00-20-18	TT	18	25A5	1125	315	8.5	810/740	3750/3350



MOTOR HOME TIRE 房车胎

1. 独特的花纹设计, 提供了良好的抓地性能, 使轮胎具有优良的高速性能。

1. The unique pattern design provides good grip performance, making the tire have excellent high-speed performance.

2. 较宽的胎面, 使轮胎具有良好的耐磨性能。

2. A wider tread provides good wear resistance to the tire.

H101/H103/H105

花纹代码 PATTERN CODE	规格 SIZE	有无内胎 TT/TL	花纹深度 DEEP (mm)	速度/速度级别 SPEED/ SPEED LEVEL	外直径 OVERALL DIAMETER (mm)	断面宽 SECTION WIDTH (mm)	标准轮辋 STANDARD RIM	气压 PRESSURE (kPa)	负荷 LOAD
H101	7-14.5-12	TL	9	100J	677	185	6	690	1060
H101	8-14.5-12	TL	11	100J	707	203	6	690	1285
H103	8-14.5-12	TL	12	100J	707	203	6	690	1285
H103	9-14.5-12	TL	12	100J	711	241	7	690	1500
H105	8-14.5-12	TL	12	100J	707	203	6	690	1285
H105	9-14.5-12	TL	12	100J	711	241	7	690	1500